



## Diesel filling stations with UNI-Tanks [PG 4]

- **Single tank**
- from HDPE with integral galvanised sheet steel bund and base pallet
- standard accessories: level gauge, visual leakage detector, integral carrying handles
- **no pump**
- for storage of diesel, biodiesel, without a bund, even in water-protected areas\*
- approved for installation **indoors**
- can be filled with delivery nozzle (except Uni-Tank 1,500 l)
- **low overall height (up to 1,000 l), thus no step tread is necessary**



UNI-Tank 1,500 l with electric pump 50 l/min see page 19



UNI-Tank 1000l

### UNI-Tank

Single tank as described above

Capacity l	Dimensions cm (l x w x h)	Approval no.	Weight approx. kg	Order no.
400	73 x 70 x 117	Z-40.21-365	50	7979
750	98 x 77 x 142	Z-40.21-288	66	7379
1000	128 x 77 x 142	Z-40.21-288	89	7380
1500	163 X 77 X 185	Z-40.21-432	151	7881

\* National installation laws and conditions are to be observed.

Accessories see pages 20.

Technical specifications subject to change.

## Diesel filling stations with UNI-Tanks [PG 4]

### Basic package 1,000 l, comprising:

- UNI-Tank 1,000 l (order no. 7380)
- electric pump 230 V, approx. 30 l/min effective (order no. 8639)
- 4 m connecting cable
- 6 m hose, may be sectioned into suction and screw delivery hose
- suction filter
- automatic delivery nozzle

### Accessory:

- K24 digital flow meter (8644) see page 110

### Basic package Premium 1,000 l, comprising:

- diesel tank UNI 1,000 l (order no. 7380)
- electric pump 230 V, self-priming, approx. 50 l/min (order no. 7768)
- pump bracket (order no. 7631)
- automatic delivery nozzle
- 4 m connecting cable
- suction hose with foot valve
- nozzle holder
- hose clamp (order no. 10252)

### Accessory:

- K33 flow meter (order no. 7779 and 7984) see page 108
- Electric flow meter FMT II/50 (order no. 7574) see page 20

### Diesel tank system with UNI-Tank 1,000l resp. 1,500l

Tank system, completely configuration comprising:

- UNI-Tank 1,000l (7380) resp. 1500l (7881), 1, 2 or 3 tanks
- filling connection with tanker coupling (7390)
- limiting value transmitter (1437),
- removal and ventilation line
- electric pump 50 l/min

### without assembly

- electric pump 230 V self-priming with automatic delivery nozzle, delivery nozzle holder, meter, 4 m filling hose and ventilation
- other lengths for filling hose optional, see page 108

- **individual filling of the tanks via fixed tanker connection**, removal and ventilation via common lines



Diesel filling station with 2 UNI-Tanks 1,500 l (order no. 8822)

### Basic packages UNI-Tank

Designation	Order no.
Basic package 1000 l	8683
Basic package Premium 1000 l	10239

### Diesel tanks systems with UNI-Tank 1,000l resp. 1,500l

Capacity l	Number of UNI-Tank 1,000 l	Delivery rate l/min	Dimensions cm (l x w x h)	Weight approx. kg	Order no.
1000	1	50	166 x 77 x 159	114	10224
2000	2	50	166 x 157 x 159	206	10225
3000	3	50	166 x 237 x 159	298	10226

Capacity l	Number of UNI-Tank 1,500 l	Delivery rate l/min	Dimensions cm (l x w x h)	Weight approx. kg	Order no.
1500	1	50	201 x 77 x 202	176	8821
3000	2	50	201 x 157 x 202	330	8822
4500	3	50	201 x 237 x 202	484	8823

Technical specifications subject to change.