



# ART. 43065

## Waste oil gravity and suction drainers

Air operated waste oil drainer 65 litre with transparent chamber



FLUIDS	WASTE OIL
SECTORS	AERONAUTIC   AGRICULTURE   AUTOMOTIVE   LUBE TRUCK AND INDUSTRIAL VEHICLE   BUILDING INDUSTRY AND ROAD CONSTRUCTION WASTE OIL
CERTIFICATIONS	PRESSURE EQUIPMENT DIRECTIVE

Features	UM	Value
Tank capacity	litres	65
Max draining capacity	litres	52
Prechamber capacity	litres	8
Bowl capacity	litres	-
Air pressure for depressurisation	bar	6,5 ÷ 7
Depressurisation time	min	2
Noise level	dB	75
Suction speed	l/min	1,5 ÷ 2
Total suction capacity	litres	43 ÷ 45
Discharging/Suction hose	m	2/2
Max pressure for discharging	bar	0,5
Set of probes	P/N	45560
Packing	N° - m <sup>3</sup>	2 - 0,230
Weight	kg	32,9
Dimensions (A-B-C)	cm	60 - 42 - 128
Dimensions (D)	cm	-

RAASM SpA

via Marangoni 33, 36022 - S. Zeno di Cassola (VI) - ITALIA  
Tel. 0039 0424 571111 - Fax. 0039 0424 571135

info@raasm.com - www.raasm.com

Copyright © 2019 All rights reserved to RAASM S.p.A.