



ART. 43114

Waste oil gravity and suction drainers

Air operated waste oil drainer 115 litre without transparent chamber



FLUIDS	WASTE OIL
SECTORS	AERONAUTIC AGRICULTURE AUTOMOTIVE LUBE TRUCK AND INDUSTRIAL VEHICLE BUILDING INDUSTRY AND ROAD CONSTRUCTION WASTE OIL
CERTIFICATIONS	PRESSURE EQUIPMENT DIRECTIVE

Features	UM	Value
Tank capacity	litres	115
Max draining capacity	litres	97
Prechamber capacity	litres	-
Bowl capacity	litres	-
Air pressure for depressurisation	bar	6,5 ÷ 7
Depressurisation time	min	3 - 3,5
Noise level	dB	75
Suction speed	l/min	1,5 ÷ 2
Total suction capacity	litres	85 ÷ 90
Discharging/Suction hose	m	2/2
Max pressure for discharging	bar	0,5
Set of probes	P/N	45560
Packing	N° - m ³	2 - 0,420
Weight	kg	42
Dimensions (A-B-C)	cm	66 - 49 - 102
Dimensions (D)	cm	-

RAASM SpA

via Marangoni 33, 36022 - S. Zeno di Cassola (VI) - ITALIA
Tel. 0039 0424 571111 - Fax. 0039 0424 571135

info@raasm.com - www.raasm.com

Copyright © 2019 All rights reserved to RAASM S.p.A.