



ART. 33173

Pneumatic pumps for oil

Pneumatic piston pump s. 650 for transferring oil and similar, R 1:1 - 40 l/min with Viton® seals and suction tube 940 mm with bung adaptor for 180-220 kg drums



FLUIDS

FRESH OIL | DIESEL FUEL

SECTORS

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | MANUFACTURING INDUSTRY | MINING

| Features | UM | Value |
|-------------------------------|---------------------|---------------------------------|
| Flow rate | l/min | 40 |
| Ratio | | 1:1 |
| Compatible fluids | | oils, lubricants and similar |
| Suction tube upper body | | aluminum |
| Suction tube | | carbon steel |
| Air inlet connection | | G 1/4" (f) |
| Fluid outlet connection | | G 3/4" (f) |
| Air working pressure | bar | 6 ÷ 8 |
| Average air consumption | l/min | 370 |
| Noise level | dB | 81 |
| max deliverable oil viscosity | SAE | 130 |
| Bung adaptor | | Standard |
| Suitable for drums or tanks | | suitable for drums 180 ÷ 220 kg |
| Packing | N° - m ³ | 1 - 0,020 |
| Weight | kg | 7,4 |
| Dimensions (A-B-C) | cm | 50,5 - 94 - 4,2 |

RAASM SpA

via Marangoni 33, 36022 - S. Zeno di Cassola (VI) - ITALIA
Tel. 0039 0424 571111 - Fax. 0039 0424 571135

info@raasm.com - www.raasm.com

Copyright © 2020 All rights reserved to RAASM S.p.A.