



## P/N 95D/61

AISI 304 stainless steel modular divorced pneumatic piston pump s. 900, R 6:1 - 42 l/min, with Teflon® seals

### AREAS OF USE

Aeronautics, Agriculture, Automotive, Building and road construction, Chemical industry, Manufacturing industry, Mining industry, Lube trucks and transports, Shipping and offshore, Railway transport

### FEATURES

|                             |                                |
|-----------------------------|--------------------------------|
| Flow rate                   | 42 l/min                       |
| Ratio                       | 6:1                            |
| Compatible fluids           | chemical and industrial fluids |
| Suction tube upper body     | AISI 304 stainless steel       |
| Suction tube                | AISI 304 stainless steel       |
| Air inlet connection        | G 1/2" (f)                     |
| Fluid inlet connection      | G 1" (f)                       |
| Fluid outlet connection     | G 3/4" (f)                     |
| Max air consumption 8 bar   | 1,6 m <sup>3</sup> /min        |
| Noise level                 | 80 dB                          |
| Max supply pressure         | 8 bar                          |
| Suitable for drums or tanks | modular                        |
| Packing                     | 1 - 0,045 m <sup>3</sup>       |
| Weight                      | 14,5 kg                        |



### OVERALL DIMENSIONS (mm)

