



Technical Specifications

Display Type	LCD
Extension Type	Flexible
Fluid Inlet Thread Gender	Female
Includes	Extension, Nozzle, Batteries, Swivel Boot
Inlet Size (cm)	1.27
Inlet Size (mm)	12.7
Inlet Thread Type	BSPP
Maximum Flow Rate (L/day)	43607.94
Maximum Flow Rate (L/h)	1816.99
Maximum Flow Rate (L/min)	30.28
Maximum Operating Temperature (°C)	70
Maximum Storage Temperature (°C)	70
Maximum Working Pressure (MPa)	10.3
Maximum Working Pressure (bar)	103.4
Maximum Working Pressure (kPa)	10340
Meter Accuracy (%)	±0.5
Meter Technology	Oval Gear
Metering Gun Weight (kg)	2.4
Minimum Flow Rate (L/min)	0.9
Minimum Operating Temperature (°C)	-16
Nozzle Type	Oil Automatic Quick-Close
Overall Length (cm)	33
Overall Length (m)	0.33
Overall Length (mm)	330
Overall Width (cm)	9.5
Overall Width (mm)	95
Product Type	Meter
Trigger Lock Type	Locking
Unit of Measure	Electronic Metered Dispense Valve Pint, Quart, Gallon, Liter

Warranty	Five Years Structural, 3 Years Electronics, 1 Year Wear Components
Wetted Material	Aluminum, Stainless Steel, PBT, Nitrile Rubber, Zinc-Plated Carbon Steel, Nickel-Plated Carbon Steel