

## CEMO petrol trolley 60 and 95 L PG 4

Petrol

- suitable for use under ADR 1.1.3.1 c) for single site refuelling by a person in the course of their main business
- container constructed from high density electrically conductive polyethylene to eliminate static
- flashback arrester
- integral grip and carry handles
- filling cap with integral breather valve
- delivery hose with stop valve
- handpump 25 L/min and nozzle
- with pump 12V, 25 L/min, automatic nozzle, 4.1 m cable with battery terminals
- trolley 95 L: 300mm diameter pneumatic tyres, air-filled, all-terrain; 3.2m conductive dispensing hose
- trolley 60 L: 240mm diameter plastic tyres; 2.7 m conductive dispensing hose
- internal baffle
- integral nozzle holder
- trolley 95 L: moulded recesses for strapping during transport



60 L with hand pump







95 L with hand pump



95 L with electric pump



Flashback arrester

Description/Capacity		Dimensions in cm (l x w x h)	Weight approx. kg	Order no.
Petrol trolley Ex0*** 60L, with hand pump		90 x 53 x 38	18	10507
Petrol trolley Ex0*** 95L, with hand pump		100 x 59 x 43	20	10162
Petrol trolley Ex0*** 60L, with electric pump		90 x 53 x 38	20	10508
Petrol trolley Ex0*** 95L, with electric pump		100 x 59 x 43	22	10646

\* explosion-suppressing insert \*\*\* with flashback arrester

## CEMO KS MOBIL EASY 120 and 190 L PG 4

ADR CERTIFIED

**KS-MOBIL Easy 120 L and 190 L certified for transport under ADR certification no. D/BAM 14341/31H2**

Examinations every 2½ years corresponding ADR 6.5.4.4.1 b\*\*\* and ADR 6.5.4.4.2.b. Completely assembled.

Container:

- single-walled 120 L or 190 L
- electrically conductive highly cross-linked polyethylene
- patented flame suppressant filling
- dipstick for checking fill level
- integral dispensing nozzle holder
- integral filler neck
- integral vent and pressure relief
- integral forklift pockets
- integral handles
- integral recesses for ratchet straps during transport

Pre-fitted pump:

- 25 L/min hand pump, 2.7 m dispensing hose (statically conductive) and manual nozzle
- self-priming pump 12V DC 25 L/min or 230V AC 40 L/min, ATEX-certified, automatic dispensing nozzle, 4 m filling hose (statically conductive) and 5 m electrical cable (pump 230V without cable)

KS-MOBIL Easy 190 L with hand pump and hinged lid



KS-MOBIL Easy 120 L with pump 12V



Explosion-suppressing insert (patent protected), hence no explosive atmosphere inside the container (120 L and 190 L)

\*\*\* The transport certification for all plastic IBCs is limited to 5 years.

# Mobile tank systems for petrol

## CEMO KS MOBIL EASY 120 and 190 L PG 4

ADR CERTIFIED

Capacity / Description	Dimensions cm (l x w x h)	Weight approx. kg	Order no.
120L with hand pump	80 x 60 x 45	23	10091
120L with pump 12V, 25 L/min, ATEX and automatic nozzle	80 x 60 x 45	33	11498
120L with hand pump and hinged lid	80 x 60 x 47	26	10092
120L with pump 12V, 25 L/min, ATEX, automatic nozzle and hinged lid	80 x 60 x 47	36	11499
190L with hand pump	80 x 60 x 59	25	10093
190L with pump 12V, 25 L/min, ATEX and automatic nozzle	80 x 60 x 59	35	11500
190L with hand pump and hinged lid	80 x 60 x 61	28	10094
190L with pump 12V, 25 L/min, ATEX, automatic nozzle and hinged lid	80 x 60 x 61	38	11501
190L with pump 230V, 40 L/min, ATEX and automatic nozzle	80 x 60 x 59	35	10458

## CEMO KS-MOBIL EASY 330 L PG 4

Petrol and petrol mixtures

**Basic and Premium versions certified for transport under ADR D/BAM 15862/31H2**

Examinations every 2½ years corresponding ADR 6.5.4.4.1 b\*\*\* and ADR 6.5.4.4.2 b.

- compact design, easy to use
- all components at optimum working height
- container made of electrically conductive, highly cross-linked polyethylene
- lockable lid with steel support stays
- flashback arrestor
- contents gauge
- integral dispensing nozzle holder
- integral filler neck
- filler cap with vent and breather valves
- integral baffle
- integral forklift pockets
- integral handles
- integral recesses for ratchet straps during transport
- with self-priming pump, 12 V DC, 25 L/min\*, with ATEX certification, automatic nozzle and 5 m cable
- fully assembled



flashback arrestor (330 L)

KS-Mobil Easy 330 L **Premium** with hose reel and galvanised steel base

### Basic version

with 4 m dispensing hose DN 19, electrically conductive, 2 m earthing conductor with terminal clamp

### Premium version

with hose reel with 10 m hose DN 19, electrically conductive, 10 m earthing conductor with terminal clamp with sturdy galvanised steel base, forklift-able from four sides



KS-Mobil Easy 330 L **Basic**

Description	External dimensions in cm (l x w x h)	Weight (approx.) in kg	Order no.
<b>KS MOBIL Easy 330 L Basic</b>	118 x 79 x 57	42	11502
<b>KS MOBIL Easy 330 L Premium</b>	144 x 80 x 67	84	11361

ACCESSORY	Order no.
Digital flow meter K24 A ATEX for mounting between dispensing hose and automatic nozzle	10411

\* Pump dispensing volume in free flow. Please note that the pump dispensing volume can fall sharply depending on the length and cross-sectional area of the hose. \*\*\* The transport certification for all plastic IBCs is limited to 5 years.